

TECHNICAL SPECIFICATIONS

MODEL	XMQ6130C
DIMENSIONS	
Length* width* height (mm)	12950x2550x3300
Wheelbase (mm)	6800
Front overhang/rear overhang (mm)	2700/3450
Minimum ground clearance (mm)	200
CAPACITY	
Seating arrangement	70+1 seats
Fuel tank capacity (L)	350
ENGINE	
Brand	Cummins
Model	ISL9E6 400
Emission standard	Euro VI
Max. Output(Kw/rpm)	265/2200
Max. Torque(N.m/rpm)	1650/1200
Displacement (L)	9
TRANSMISSION & CLUTCH	
Transmission	VOITH AUTOMATIC
Clutch	NO
RETARDER	
Retarder	ZF incorporated intarder
AXLES	
Front	FANG SHEN front indenpent axle
Rear	FANG SHEN rear axle
SUSPENSION	
Suspension system	6-air bag suspension
ECAS	WABCO
STEERING	
Steering system	ZF hydraulic power steering gear



Headlight modeling is stylish and fashionable.



Up round and down square, a perfect harmony elegance and strength, matched with taillight, which makes the whole bus eye catching.

BRAKE	
Brake system	Full disc brake
Tyre	MICHELIN tubeless tyre (295/80R22.5)/XZA2+
DOOR & WINDOW	
Doors	Aluminum, remote control, front single out swing & middle double out swing doors
Side windows	Full sealed side windows, with privacy toughened glass
SEATS	
Driver	Chinese adjustable Damping Suspension Driver Seat, ISRI as option
Passenger	FAINSA STEL passenger seat
AV EQUIPMENT	
Equipment	ACTIA DVD
Monitoring system	Color reverse monitor, reverse radar
AIR CONDITIONER	
Type	A/C Roof mounted, dependent
HEATER	
Type	SPHEROS heater
MIRROR	
Type	Electric rear view mirror with defroster
OTHER STANDARD EQUIPMENTS	
VDO CAN BUS system, VDO digital tachograph with print & display, electrically elevated driver window with defroster, automatic fire extinguisher for engine compartment, step lamp, reading lamp, with wheel chair lift	